

Product Catalog

2026

Our Services



Merchanting

Professional lighting, no middlemen

- ✓ Supply
- ✓ Certified Product
- ✓ Modernization
- ✓ 5-Year Warranty
- ✓ Regulatory Compliance
- ✓ Financing



Basic Glow

Lighting ready to operate

- ✓ Supply
- ✓ Installation
- ✓ Certified Product
- ✓ Modernization
- ✓ 5-Year Warranty
- ✓ Regulatory Compliance
- ✓ Financing
- ✓ Site Visit



Essential Glow

Lighting and protection system

- ✓ Supply
- ✓ Installation
- ✓ Certified Product
- ✓ Modernization
- ✓ 5-Year Warranty
- ✓ Regulatory Compliance
- ✓ Financing
- ✓ Site Visit
- ✓ Diagnostics and Lighting Study
- ✓ Implementation Schedule
- ✓ Corrective Maintenance
- ✓ Guaranteed Response Within 48 Hrs*
- ✓ CECODAP Remote Management and Monitoring
- ✓ Extended Warranty



Basic 360°

Lighting without breaking the bank

- ✓ Supply
- ✓ Installation
- ✓ Certified Product
- ✓ Modernization
- ✓ 5-Year Warranty
- ✓ Regulatory Compliance
- ✓ Financing
- ✓ Site Visit
- ✓ Diagnostics and Lighting Study
- ✓ Implementation Schedule
- ✓ Corrective Maintenance
- ✓ Preventive Maintenance
- ✓ CECODAP Remote Management and Monitoring
- ✓ 95% Efficiency
- ✓ Unlimited Light Bulbs
- ✓ 72-Hour Repair



360°

ZERO worries

- ✓ Supply
- ✓ Installation
- ✓ Certified Product
- ✓ Modernization
- ✓ 5-Year Warranty
- ✓ Regulatory Compliance
- ✓ Financing
- ✓ Site Visit
- ✓ Diagnostics and Lighting Study
- ✓ Implementation Schedule
- ✓ Corrective Maintenance
- ✓ Preventive Maintenance
- ✓ CECODAP Remote Management and Monitoring
- ✓ 95% Efficiency
- ✓ Unlimited Light Bulbs
- ✓ 72-Hour Repair
- ✓ Energy Bill Payment

Industrial

Custom lighting for industrial areas.



HGX

15,168 a 40,200 lm

Bell-shaped LED light fixture, designed for high-ceiling installation. Its high performance and excellent illumination make this product one of the most effective solutions for industrial lighting.



Certification	NOM
Power	107W - 130W - 170W - 192W - 218W - 233W - 248W
Lumen Range	15,168 - 40,200 lm
CRI	≥80
Protection Rating	IP65
Voltage	120 - 277V~
Color Temperature	4,000K - 5,000K
Warranty	Up to 5 years

HCX - PRO

9,600 a 30,000 lm



Bell-shaped LED light fixture, designed for high-ceiling installation. Its excellent illumination makes this product one of the most effective solutions for industrial lighting.

Certification	CE, NOM, RoHS
Power	60W - 80W - 90W - 100W - 110W - 120W - 150W - 200W
Lumen Range	9,600 - 30,000 lm
CRI	≥80
Protection Rating	IP65
Voltage	100 - 277V~
Color Temperature	4,000K - 5,000K - 6,500K
Warranty	Up to 5 years

HBX

12,400 a 59,800 lm

High Bay-style industrial LED light fixture, designed for industrial settings and workspaces; this high-mount fixture offers excellent performance with over 200 lm/W, reducing fixed costs from the moment of installation with an unbeatable ROI.



Certification	DLC, DLC Premium, NOM
Power	64W - 81W - 95W - 102W - 123W - 139W - 154W - 168W 206W - 262W - 310W
Lumen Range	12,400 - 59,800 lm
CRI	≥70
Voltage	120 - 277V~
Color Temperature	4,000K - 5,000K
Warranty	Up to 5 years

HBX – G6

16,800 a 102,000 lm



High-efficiency LED high-bay light fixture. Improves lighting levels in work areas with an innovative, compact, lightweight design that is easy to install and offers superior performance.

Certification	NOM
Power	80W - 100W - 139W - 158W - 179W - 199W - 239W 258W - 316W - 352W - 398W - 478W - 516W
Lumen Range	16,800 - 102,00 lm
CRI	≥70
Voltage	120 - 277V~
Color Temperature	4,000K - 5,000K
Warranty	Up to 5 years

WPL

7,200 a 21,600 lm

LED wall pack with COB (Chip On Board) technology, providing more uniform and efficient light output with excellent heat dissipation. It features a hinged frame for easy maintenance access.



Power	40W, 50W, 60W, 100W, 120W
Lumen Range	7,200 - 21,600 lm
CRI	≥70
Protection Rating	IP66
Voltage	120 - 277V~
Color Temperature	4,000K - 5,000K
Warranty	Up to 5 years

Commercial

Lighting for commercial areas, booths, and educational spaces.



SDL - 321

2,580 a 11,167 lm

LED light fixture, ideal for mid-level or low-level installation. It provides excellent illumination while offering high visual comfort thanks to its aesthetic and innovative design.



Power	20W - 30W - 45W - 63W - 83W
Lumen Range	2,600 - 11,100 lm
CRI	≥80
Protection Rating	IP40
Voltage	120 - 277V~
Color Temperature	3,000k - 4,000K - 5,000K
Warranty	Up to 5 years

LIN

4,150 a 13,881 lm

Linear luminaire with a tandem-style design for in-line installation. Suitable for surface-mounted or suspended installation, with optimal light distribution thanks to its matte opal diffuser.



Certification	NOM
Power	30W - 31W - 39W - 49W - 62W - 78W - 98W
Lumen Range	4,150 - 13,881 lm
CRI	≥80
Voltage	120 - 277V~
Color Temperature	3,000k - 4,000K - 5,000K
Warranty	Up to 5 years

SLSX

4,850 a 16,224 lm

The **tandem linear fixture** offers exceptional efficiency for mid- or high-level installation, with optimal light distribution thanks to its matte opal diffuser and an electronic driver that stabilizes the voltage.



Power	30W - 39W - 40W - 49W - 50W - 60W - 80W - 100W
Lumen Range	4,850 - 16,224 lm
CRI	≥70
Voltage	120 - 277V~
Color Temperature	5,000K
Warranty	Up to 5 years

Outdoor Area Lighting

Lighting for outdoor areas, parking lots, building facades, and recreational areas.



EG – FL

13,000 a 26,000 lm



LED floodlight designed to withstand demanding outdoor conditions without compromising performance, ensuring reliable, safe, and long-lasting outdoor lighting.

Power	100W - 150W - 200W
Lumen Range	13,000 - 26,000 lm
CRI	≥75
Protection Rating	IP66
Voltage	100 - 277V~
Color Temperature	3,000K - 6,000K
Warranty	Up to 5 years

SLED - 990

15,128 a 90,769 lm

Modular LED Floodlight. Features rotating modules to direct the light, each rated at 100W, with scalable models up to 600W. It features a 90° lens that is resistant to high temperatures and UV rays.



Certification	NOM
Power	100W - 200W - 301W - 401W - 601W
Efficiency	151 lm/W
Lumen Range	15,128 - 90,679 lm
CRI	≥70
Voltage	120 - 277V~
Color Temperature	5,000K
Warranty	Up to 5 years

LPT – PRO

5,670 a 12,300 lm

High-efficiency LED canopy light fixture capable of adjusting the color temperature to suit the desired ambiance. Compact design that is easy to install and delivers maximum performance.



Certification	DLC, FCC, NOM, RoHS, UL
Power	45W - 70W - 100W
Efficiency	128 lm/W
Lumen Range	5,670 - 12,300 lm
CRI	≥70
Voltage	120 - 277V~
Color Temperature	3,000k - 4,000K - 5,000K
Warranty	Up to 5 years

EG – ST20

8,700 a 21,750 lm



A pole-top luminaire featuring the latest in state-of-the-art LED technology, providing excellent illumination through its optical design and ensuring uniform light distribution throughout the area.

Certification	NOM
Power	60W - 80W - 100W - 120W - 150W
Lumen Range	8,700 - 21,750 lm
Voltage	100 - 277V~
Color Temperature	3,000K - 4,000K - 5,000K - 5,700K
Warranty	Up to 5 years

Street Lighting

Lighting for roads, avenues, and public spaces.

04.



LIT – BS

4,800 a 19,200 lm



LED streetlight designed to deliver high performance, energy efficiency, and a long service life. It features excellent luminous efficiency, uniform light distribution, and low energy consumption.

Power	30W
Efficiency	160 lm/W
Lumen Range	4,800 lm
CRI	≥70
Voltage	100 - 277V~
Color Temperature	5,000K - 5,200K
Warranty	Up to 5 years

LIT - BS

4,800 a 19,200 lm



High-performance LED luminaire designed for higher luminous flux and energy efficiency requirements. Equipped with a dual-module LED optical system and a high-strength aluminum housing.

Power	50W - 80W
Efficiency	160 lm/W
Lumen Range	8,000 - 12,800 lm
CRI	≥70
Voltage	100 - 277V~
Color Temperature	5,000K - 5,200K
Warranty	Up to 5 years

LIT - BS

4,800 a 19,200 lm

An LED luminaire from the LIT - BS family, offering superior performance for the most demanding projects. It features efficient thermal management and precision optics, providing uniform lighting, a long service life, and reliable performance.



Power	100W - 150W
Efficiency	160 lm/W
Lumen Range	16,000 - 19,200 lm
CRI	≥70
Voltage	100 - 277V~
Color Temperature	5,000K - 5,200K
Warranty	Up to 5 years

LIT – BS II

5,400 a 27,000 lm

LED streetlight that represents the evolution of our Lichttek line of luminaires. The perfect solution for uniform lighting, greater coverage, and lower energy consumption.



Power	30W - 50W - 80W
Efficiency	180 lm/W
Lumen Range	5,400 - 14,400 lm
CRI	≥70
Voltage	100 - 277V~
Color Temperature	5,000K - 5,200K
Warranty	Up to 5 years

LIT – BS II

5,400 a 27,000 lm

High-efficiency LED luminaire. The best choice for modernizing street lighting, offering excellent performance and energy efficiency thanks to an advanced heat dissipation system and high optical performance.



Power	100W - 120W - 150W
Efficiency	180 lm/W
Lumen Range	18,000 - 27,000 lm
CRI	≥70
Voltage	100 - 277V~
Color Temperature	5,000K - 5,200K
Warranty	Up to 5 years

HSL5

6,600 a 33,000 lm

High-efficiency LED streetlight. Compatible with 3-pin and 5-pin photocells. Compact and lightweight design, making it easy to install in accordance with national standards.



Certification	NOM 031
Power	40W - 50W - 60W - 80W - 100W - 120W - 150W - 200W
Efficiency	165 lm/W
Lumen Range	6,600 - 33,000 lm
CRI	≥70
Voltage	IK08, IP66
Color Temperature	5,000K
Warranty	Up to 5 years

SUNEL

7,600 a 22,800 lm

Pole-mounted light fixture with an integrated photovoltaic system. Its sturdy aluminum structure and motion sensor provide greater performance and energy savings. It is mounted on an adjustable-angle arm.



Certification	NOM, ANCE
Power	40W - 60W - 80W - 120W
Lumen Range	7,600 - 22,800 lm
Solar Panel (Mono)	42W - 120W
Battery Capacity	346 - 460 - 691WH
Protection	IP67
Color Temperature	6,000K
Warranty	Up to 5 years

Corporate Headquarters

(+52) 81 1004 9491 

www.lichttek.com 

comercial@lichttek.com 

Torre Hélicon, San Pedro Garza García, N.L. 

Centro-Bajío Sales Office

(+52) 442 878 7041 

(+52) 452 255 099 36 

www.lichttek.com 

comercial.bajio@lichttek.com 

World Trade Center Querétaro, Piso 6, Oficina 607, Paseo de la República
Km13020, Juniquilla, 76230 Santiago de Querétaro, Querétaro. 